



1



2

AVM-01 / 03 Anemometer

- Sensitive and accurate
- Ergonomic and easy-to-use design
- Air velocity (m/s, ft/min, knots, km/hr)
- AVM-03: Air temperature (0°C~60°C or 32°F~140°F)
- AVM-03: Max hold for temperature

- Data hold function
- Large 17mm 3 ½ digits LCD
- 2-meter coiled cable and mounting nut
- Build-in low battery indicator

Range of Wind Velocity:

Unit	Range	Resolution	Threshold	Accuracy
m/s	0.0 - 45.0	0.1	0.3	±3% ± 0.2
ft/min	0 - 8800	10	60	±3% ± 40
knots	0.0 - 88.0	0.1	0.6	±3% ± 0.4
Km/hr	0.0 - 140.0	0.1	1.0	±3% ± 0.8

AVM-05 / 07 Flow Anemometer

- Sensitive and accurate
- Ergonomic and easy-to-use design
- Air velocity (m/s, ft/min, knots, km/hr, mph)
- Air flow (CMM, CFM)
- Air temperature (0°C~45°C or 32°F~113°F)
- LCD dual display (VEL + temperature, FLOW + AREA)
- Data logging function with max. 2000 records

- Sampling time set by keypad
- Hold/ Max/ Min function
- Large 17mm 9999 digits LCD
- 2-meter coiled cable and mounting nut
- Built-in low battery indicator
- AVM-07: USB interface with PC

Range of Wind Velocity:

Unit	Range	Resolution	Threshold	Accuracy
m/s	0.0 - 45.0	0.01	0.3	±3% ± 0.1
ft/min	0 - 8800	2	60	±3% ± 20
knots	0.0 - 88.0	0.02	0.6	±3% ± 0.2
Km/hr	0.0 - 140.0	0.04	1.0	±3% ± 0.4
mph	0.0 - 100.0	0.02	0.7	±3% ± 0.2