



4 Wires Alligator Clip

## RP-91

- Using On Bench Type LCR Meter.
- Compatible On All Brands Bench Type LCR Meter.
- 4-Wire Leads Compensate Internal Impedance Error.



## RP-92

- High shield rate, low noise design, It remains steady and measurable even the capacitor which is lower than 1pF.
- It supports multiple accessories to suit for different components.
- The probe tip can be replaced to extend the life of the product.
- It is high efficiency and cost effective.
- Cable Length: Approx. 0.8Meter (from connector to probe tip).
- Terminal connection: BNC, 4 terminal-pair.

## MT-246N



- BNC connects to the specialized adapter of the banana plug.
- PL-10 exclusive accessory.
- Red and Black plastic isolation cover are convenient to recognize positive and negative electrodes.
- The end of banana plug uses beryllium copper to prevent bad connection.
- Accord with CE norm. It is safe and reliable.
- The maximum working voltage 300V CAT2. 3A.1GHz.
- Length: 70mm. Width: 28mm. Weight: 19g.

**BP-250**

BNC Plug to BNC Plug  
(50 Ω RG58C UL, 100 cm,  
1G Hz, 3A)

**BP-251**

BNC Plug to  
Alligator Plug  
(RG58C UL, 115 cm,  
1G Hz, 3A)

**BP-253N**

Banana Plug to  
Alligator Clip  
(UL 3239, 18AWG,  
6KV DC, 10A, 150°C,  
Silicone Wire, 100 cm )

**BP-356N**

Banana Plug to  
Banana Plug  
(UL 3239, 18AWG,  
6KV DC, 10A, 150°C,  
Silicone Wire, 60 cm )

**BP-366**

HV Banana Plug to  
Banana Plug  
(UL 3239, 16AWG,  
20KV DC, 10A, 150°C,  
Silicone Wire, 60 cm )

**BP-256N**

IC Clip  
(UL 1000V CAT III, 5A)

**BP-266**

HV IC Clip  
(MAX. 7KV RMS, 5A)

**BP-276N**

Alligator Clip  
(UL 1000V CAT III, 10A)

**BP-286N**

Test Leader  
(UL 94V-2,  
1000V CAT III, 10A,  
φ 11.5x120mm)

จัดจำหน่ายโดย : บริษัท เฟเวอร์เทค จำกัด  
TEL : (02)8702884-5, (02)4289793-5  
Email: sales@evertech.co.th  
www.evertech.co.th