



CE

ST-365 TR

DC Volts : 0-0.01/0.5/2.5/10/50/250/1000V(20kΩ/V)
 AC Volts : 0-10/50/250/1000V
 DC mA : 50uA/2.5/25/250mA
 OHMS : 2K/20K/200K/2M/20M (20 Mid-Scale)
 Accuracy : ±3% F.S. DC. ±4% F.S. AC.
 Sensitivity : 20kΩ/V DC. 8kΩ/V AC.
 DB : -10 to ±50dB
 Hfe : 0-1000
 ICEO : 150uA, 1.5mA, 15mA, 150mA
 LV : 3V
 Dimension : 100(L) x 150(W) x 41(D)mm
 Weight : 300g
 Power : Two "AA" 1.5V Batteries.
 One 006P 9V Battery.

● IEC 1010-1 CAT.II 1000V



CE

ST-360 TRn

DC Volts : 0-0.01/0.5/2.5/10/50/250/1000V(20kΩ/V)
 AC Volts : 0-10/50/250/1000V
 DC mA : 50uA/2.5/25/250mA
 OHMS : 2K/20K/2M/20M (20 Mid-Scale)
 Accuracy : ±3% F.S. DC. ±4% F.S. AC.
 Sensitivity : 20kΩ/V DC. 8kΩ/V AC.
 Db : -10 to ±50dB
 Hfe : 0-1000
 ICEO : 150uA, 15mA, 150mA
 Lv : 3V
 Dimension : 102(L) x 148(W) x 46(D)mm
 Weight : 300g
 Power : Two "AA" 1.5V Batteries.
 One 006P 9V Battery.

● IEC 1010-1 CAT II 1000V



ST-520

● For telecom and audio work,

DCV : 0-0.25/1/2.5/10/25/100/250/1000V
 (50kΩ/V) ±3%
 ACV : 0-2.5/10/25/100/250/500/1000V
 (13kΩ/V) ±4%
 DCA : 0.05/5/50/500mA. 0-12 ±3%
 Resistance : 2kΩ, 20kΩ, 2MΩ, 20MΩ
 (Midscale 20, 200, 20k, 200kΩ)
 Decibel : -20 to 56dB(0dB=1MW, 600Ω)
 Dimension : 110(L) x 160(W) x 52(D)mm
 Weight : 480g
 Power : Two "AA" 1.5V Batteries.
 One 006P 9V Battery.



จัดจำหน่ายโดย : บริษัท เอฟเวอร์เทค จำกัด

TEL : (02)8702884-5, (02)4289793-5

Email: sales@everttech.co.th

www.everttech.co.th