

1362 Printing Humidity/Temperature Meter



TES-1362 Printing Humidity Temperature Meter

FEATURES :

- Triple LCD Display for RH% Humidity, T₁ for Air Temperature and T₂ Type K Thermometer (-200°C~1333°C)
- Dew Point Reading
- Max / Min / Data Hold
- Real Time Stamp
- Periodically Print out from Pre-Set time Interval

SPECIFICATIONS:

Measuring Range	T ₁ : Temperature : -20°C ~ 60°C (-4°F ~ 140°F) Humidity : 10%RH ~ 95%RH T ₂ : Type K : -200 ~1333°C (-58 ~ 2431°F)
Resolution	0.1°F/0.1°F/0.1%RH
Accuracy	T ₁ : Temperature : ±0.8°C, ±1.5°F Humidity : ±3%RH (at 25°C, 30....95%RH) T ₂ : Type K : -50°C ~ 500°C, (0.1%rdg + 0.8°C) 500°C ~ 1333°C, (0.2%rdg + 1.8°C)
Input Protection	60V DC or 24 Vrms AC maximum input voltage on any Combination of input Connector.
Sampling Rate	1 time/sec
Operating Conditions	0°C ~ 40°C (32°F ~ 104°F) 10 ~ 80% R.H.
Power Source	6 pcs size AAA Alkaline Battery or 9V DC adaptor/500mA minimum.
Battery Life	Approx. 30 hours.(interval printing = 60 minute, not including beeper). 70 hours (except printing & beeper).
Size	193(L) x 74(W) x 37(H)mm
Weight	Approx. 385g
Accessories	1. Carrying case, Instruction manual, Battery, type K probe (TP-K01). 2. Two rolls thermo-paper. 3. Humidity / Temperature Probe.



จัดจำหน่ายโดย : บริษัท เอฟเวอร์เทค จำกัด
TEL : (02)8702884-5, (02)4289793-5
Email: sales@evertech.co.th
www.evertech.co.th

TES

TES ELECTRICAL ELECTRONIC CORP.

7F, No.31 Lane 513, Rui Guang Rd., Neihu Dist, Taipei, Taiwan, R.O.C.

Tel : (02) 2799-3660 Fax : 886-2-2799-5099

E-mail : tes@ms9.hinet.net <http://www.tes.com.tw>