

TM-183P



SPECIFICATIONS

- Display : Dual LCD display. The maximum value on the primary display is 1999.
- The maximum value on secondary display is 9999.
- Low Battery Indicator : When the LCD displays symbol, please replace the battery.
- Sampling Rate : 1 sample per second.
- Power Supply : One 9V battery, NEDA 1604, IEC 6F22 or JIS 006P.
- Battery Life : 200 hours during consecutive use.
- Dimensions : 130 × 56 × 38 mm (L × W × H)
- Weight : 200g (excluding the battery)
- Accessories : User manual, battery, carrying case , Temperature and humidity probe(TM-183P).
- Operating Temperature and Humidity :
0°C ~ +60°C, <95% RH. (non-condensing)
- Storage Temperature and Humidity:
-10 to 60 °C, <70% RH. (non-condensing)

Electrical Specification : (Temperature: 25°C, Humidity : <90% RH)

- Temperature Measurement Range : -40.0°C ~ +60.0°C (-40.0°F - +140.0°F).
- Humidity Measurement Range : 0% ~ 100%RH.

Accuracy:

- Humidity : ± 3% (20~80%RH, @25°C)
± 5% (<20% >80%, @25°C)
- Temperature : ± 0.8°C, ± 1.5°F.



จัดจำหน่ายโดย : บริษัท เฟเวอร์เทค จำกัด
TEL : (02)8702884-5, (02)4289793-5
Email: sales@evertech.co.th
www.evertech.co.th