

TENMARS



TM-801 / TM-802 CO Meter

Features :

- Audible alarm : Adjustable alarm threshold level (25/35/50/100/250/400/800/ Randomly); Enable / Disable alarm.
- Max. / Avg/Min. HOLD
- Data Hold.
- LCD Display with Backlit.
- Auto. Power Off and disable function.
- Easy to Calibration (100 ppm or 500 ppm).
- Simultaneously display of the CO (Carbon monoxide) and Temperature.
- USB Interface; PC Software.(TM-802)
- Auto data logger up to 32000 records. (TM-802)
- Selectable Logging Rate. (TM-802)
- Start Logging by Date& Time/Delay/Immediate. (TM-802)

Specification :

CO Range	0 ~ 1000 ppm	Temperature Range	-20~50°C / -4~122°F
Resolution	1 ppm	Resolution	0.1°C / 0.1°F
Accuracy	±5%	Accuracy	±1.0°C / 1.8°F
Response	time 30 seconds		
Dimension	156x73x35 mm(LxWxH).		
Weight	250g		
Power	LR6 (AA)1.5V x6 batteries		



จัดจำหน่ายโดย : บริษัท เอฟออร์ท เทคโนโลยี จำกัด
TEL : (02)8702884-5, (02)4289793-5
Email: sales@evertech.co.th
www.evertech.co.th

TENMARS ELECTRONICS CO., LTD
6F, 586, RUI GUANG ROAD, NEIHU,
TAIPEI 114, TAIWAN.

E-mail: service@tenmars.com
http://www.tenmars.com